

Improving steering system for walking tractor-trailer combination to increase operator's comfort and ease of control

Ali Mirzakhani Nafchi¹, Hassan Mirzakhani Nafchi², Iman Abdollahi Demneh²

(1. Farm Machinery Department, Shahrekord University, No. 179, Baharestan St. Nafch, Shahre kord, Iran;

2. Farm Machinery, Faculty Member of G.I.CO)

Abstract: The aim of present study was to develop the performance of walking tractor-trailer combination, increase the ability of control and steering, maneuverability, reduce the hand transmitted vibration (HTV), discomfort, stress and probability of accident for walking tractor operators. The location of controls in existing walking tractor with respect to anthropometric suitability of operators and rearrangement for improved operator's ergonomics was analyzed. To compare existing system with improved system, and find the affects of improved workplace layout over the existing one in terms of physiological cost and discomfort of the walking tractor operator, turning radius, operator hart rate, energy cost and HTV were measured. The energy cost of riding walking tractor-trailer with improved workplace layout is 9.2% lesser than that of riding unmodified walking tractor-trailer. The overall discomfort and body part discomfort of operator riding walking tractor-trailer with improved workplace layout were reduced by 38.5 and 17.9% walking tractor-trailer with and without improved work space layout. The HTV was measured and analyzed as per the guidelines of International Standards ISO 5349 (1986 Vibration was measured using the portable four-channel multi-analyzer system. The data collection included frequency-unweighted and frequency-weighted vibration in RMS acceleration, frequency response of the vibration. The HTV reduction of the walking tractor with trailer at the handles for steering system was improved from 10.1 to 11.6% and from 11.9 to 17.3% on farm road and concrete road respectively at selected levels of forward speed of operation. The turning radius decrease from 6.2 to 2.7, 6.7 to 2.8 and 7 to 3 meters for unmodified and modified walking tractor respectively at the speed of 3, 4 and 5 km/h. Average operator hart rate has reduction at the rate of 20% for modified compared to unmodified walking tractor. Reduction in operator heart rate was because of fixing the handle steering and convenience during the operating.

Keywords: walking tractor, steering, workplace layout, vibration, heart rate, turning radius

Citation: Ali Mirzakhani Nafchi, Hassan Mirzakhani Nafchi, Iman Abdollahi Demneh. 2011. Improving steering system for walking tractor-trailer combination to increase operator's comfort and ease of control. Agric Eng Int: CIGR Journal, 13(3).

1 Introduction

The walking tractors are used in very many areas as well as rice and sugarcane producing areas. The operators of hand tractors experience high levels of vibration in the hand and arm, which cause early fatigue and result in shorter work hours. So the operator of a walking tractor has to endure various environments and stresses. Agricultural workers have different anthropometric dimensions, perception of comfort, strength, sensory capabilities, mental or cognitive

capabilities for storing and training. So their processing information, making decisions, experiences, motivation, cultural background, perception of risks etc., are different from the industrial workers. Nowadays researchers are placing attention to ergonomic aspects of the farm workers and this proposed research work to be carried out is also another step towards changing to betterment of walking tractor operators. The ergonomic aspects of walking tractors are of great importance as working with walking tractor involves considerable physical strain to the operator. The working performance of a walking tractor depends not only on the machine but also on the operator. If ergonomic aspects are not given due consideration, the performance of the man-machine

Received date: 2009-12-29 Accepted date: 2011-12-11

Corresponding author's email: mirzakhanafchi.ali@gmail.com

system will be poor and effective working time will be reduced. The man-machine environment system of walking tractor operation indicates that the operator of a walking tractor has to endure various environments and stresses. Among these factors, environment is more important because it significantly accelerates fatigue and affects sensitivity and reaction heart rates of the operator. Controlling the walking tractor with trailer while turning causes considerable fatigue to the operator.

2 Review of literature

The operators of walking tractors experience high levels of vibration in the hand and arm, which cause early fatigue and result in shorter work hours. The operator of a walking tractor has to endure various environments and stresses. The various disorders associated with exposure to vibration are vascular, neurological, musculoskeletal, and other effects. The term 'hand-arm' vibration syndrome (HAVS) is used collectively for the different symptoms of the disorder (Mishoe and Suggs, 1977; Reynolds and Keith, 1977; Wasserman and Taylor, 1991). Frequency-weighted vibration acceleration of a moving component either reciprocating or rotating causes vibration depending on its own degree-of-freedom and the natural frequency. A machine consists of many such moving components which contribute to the further vibration of the whole system. This interference of vibration makes the vibration of the whole system rather complex. Thus machines produce a most dominant frequency of vibration and subsequent frequencies of vibration are observed at a periodic interval. However, human response to hand-arm vibration varies enormously for frequencies between 6.3 and 1,250 Hz. At low frequency lesser than 100 Hz, the vibration is transmitted from the handle to hands, arms and shoulders without attenuation and therefore the perception is high. The perception greatly decreases with the increasing of the frequency and the reduction of vibration transmissibility throughout the hand-arm system (Broyde et al., 1989; Giacomina et al., 2004). The international standard ISO 5349 (ISO, 2001) recommends the use of frequency-weighted acceleration. To establish the stress potential

of particular work, it may also be necessary to consider the working posture and environmental parameters such as temperature, humidity, noise and dust levels. Grandjean (1988) has suggested that the measurement of stress at work must focus on the individual's psychological state. Psychophysical methods are one of the methods used to determine acceptable workloads (Snook and Ciriello, 1991; Garg et al., 2006). Psychophysical self-rating based on Borg scale, CR-10 (Borg, 1982) has been used for measurement of perceived stress. Wos et al. (1988) have found that self-rating based on Borg's scale can be used to assess vibration intensity. The pictorial representations, where discomfort is plotted on a human figure, have been used for studies of vibration tolerance and discomfort and also for studies of back pain (Kuorinka, 1983).

3 Materials and method

The field experiment and the ergonomics refinement was carried out in the steering system include:

As illustrated in Figure 1, the two handle bars attached to the body of a 7 Hp diesel walking tractor are removed and rigidly fitted in front of the toe bar of the trailer with a bracket. The handle bars are supported with fixtures from the toe bar of the trailer. The main clutch and brake lever from the handle bar of the walking tractor is connected to the clutch assembly through a rod and cable supported by clamps mounted on the left side handle bar. The two steering cables were extended in linear mode through a coupling mounted on the two sides of the bracket mounted on toe bar of the trailer. The steering cable consists of two portion *i.e.*, one is connected between the steering clutch and the coupling and the other connected between the coupling and steering lever in the body of the walking tractor.

Assessment of ergonomic parameters and physical work load for comparing modified walking tractor with the unmodified HR was taken as a reliable index. Selected subject was given enough of rest and then their resting heart was measured with the heart rate monitor. After the complete rest, the subjects were asked to perform operating the walking tractor. During the

operating the heart rate was recorded every 10 seconds. To evaluate total physiological expenditure, physiological reaction, both during the work load (activity) and during the recovery period are considered. Heart rate was recorded using Mounting Polar Electro Oy Pacer heart rate monitor on the body firstly at rest, during the activity and recovery. From the value of HR, total cardiac cost of work (TCCW) and physiological (PCW) for walking tractor operation was calculated.



Figure 1 7 hp diesel walking tractor with removed handles from body and rigidly fitted in front of the toe bar of the trailer with a bracket

3.2 Ergonomic evaluation

Ergonomic evaluation of walking tractor with improved work place layout was conducted with selected 12 male subjects. The subjects were screened for normal health through medical investigations. The age, mass and height of the selected male subjects were 29.9 ± 3.6 years, 60.9 ± 3.4 kg and 160.4 ± 6.3 cm respectively. The selected twelve subjects were calibrated in the laboratory by indirect assessment of oxygen uptake. The maximum aerobic capacity of the selected twelve male varied from 1.90 to 2.26 l min⁻¹. The ergonomic evaluation was conducted to ascertain the improved comfort, safety and ease of operation. The trials were conducted between 10.00 AM to 5.00 PM during the October 2009. The temperature and relative humidity varied from 24 to 28 °C and 69 to 76 % respectively during the period of evaluation. The evaluation was carried out in terms of hand transmitted vibration, heart rate (HR), oxygen consumption rate (OCR), energy cost of operation (ECR), acceptable work load (AWL), limit of continuous performance (LCP), overall discomfort rating (ODR), overall safety rating (OSR), overall rating

of ease of operation (OER), body part discomfort score (BPDS) and vibration transmitted to the operator. The mean values of discomfort, safety and ease of operation rating of the subjects are furnished in Table 1 as below.

Table 1 Mean values of discomfort, safety and ease of operation rating of the subjects

walking tractor operation	Rating	ODR Scale
A. Overall discomfort rate (ODR)		
walking tractor -trailer without improved work place layout	6.5	< More than discomfort. < 5
walking tractor -trailer with improved work place layout	4	< Moderate discomfort 3.5 to 5
B. Overall safety rating (OSR)		
walking tractor -trailer without improved work place layout	5.5	< Less inconvenient and less unsafe. < 5
walking tractor -trailer with improved work place layout	4.5	> Less convenient and less safe. 4 to 5
C. Overall ease of operation rating (OER)		
walking tractor -trailer without improved work place layout	5.8	Less inconvenient and less unsafe. < 5
walking tractor -trailer with improved work place layout	3.1	> Moderately convenient and moderately safe. > 3.5

The cost of riding walking tractor-trailer with improved work place layout is 9.2% lesser than that of riding walking tractor-trailer without improvement. The mean values of oxygen consumption rate (OCR) in terms of VO₂ max and the work pulse values were much higher than that of the AWL limit of 35% of VO₂ max and higher than the LCP value of 40 beats min⁻¹, which is clear indicative of the fact that the walking tractor-trailer operation could not be performed for longer duration without adequate rest. Mean values of body part discomfort score of the subjects for walking tractor-trailer operation are furnished in Table 2.

Table 2 Body part discomfort for walking tractor-trailer operation

	BPDS	Score
Modified walking tractor -trailer	Heavy pain in left and right shoulders, mid back and neck. Moderate pain in lower back and neck	39
Unmodified walking tractor -trailer	Moderate pain in left and right shoulders, mid back and neck. less pain in lower back and neck	32

The overall discomfort and body part discomfort of operator riding walking tractor-trailer with improved work place layout is reduced by 38.5 and 17.9% respectively when compared with walking tractor-trailer

without improvement. The walking tractor-trailer with improvement resulted in 18.2 and 46.6% increase in safety and ease of operation when compared with riding walking tractor-trailer without improvement. The modified steering system in modified walking tractor-trailer arrested the relative motion of the operator between the trailer seat and steering handle and the up and down swing motion of the handle bar. Controls *viz.*(such as), steering clutch, main clutch lever, brake lever, main gear shift lever and rotary gear shift lever are well within the reach of the operator. The mean values of physiological response of the subjects for walking tractor –trailer operation are furnished in Table 3.

Table 3 Mean values of physiological response for walking tractor operation

walking tractors	Heart rate beats min ⁻¹	Energy cost /kJ·min ⁻¹	AWL (35% VO ₂ max)	LCP beat min ⁻¹
walking tractor-trailer without improved work place layout	136.1	27.1 (Heavy)	61.7 (> AWL)	48.2 (>LCP)
walking tractor –trailer with improved work place layout	125.6	24.6 (Heavy)	56.1 (>AWL)	43.8 (>LCP)

3.3 Steering system for walking tractor trailer

The steering wheel serves two purposes: *viz.* to transmit steering forces and to support the body of the operator. The steering handles position allows the operator's back to be braced against the lower backrest at all times. The arm each encourages grasping the sides of the steering handles for maximum stabilization. The elbow should remain partly flexed permitting the upper arms position to hang freely close to the side. If the plane of steering handle is between approximately 30° to 45° from the horizontal the operator's forearm rests on the steering handle for relaxation without pulling the shoulder girdles forward into a round shouldered position. The elbow and shoulder joints are capable of extreme mobility. However, an excessive reach to the steering handle places burden on the muscles, which hold the arm up against gravity. The location of controls in walking tractor with and without improved work place layout for walking and riding type walking tractor with reference to the seat rest are measured and the values are furnished in Table 4.

Table 4 Location of controls in walking tractor with and without improvement

Serial No.	Locations of controls	Walking tractor with trailer	
		Without replaced	With improved
i	Distance between seat rest and handle, mm	710	500
ii	Minimum distance between seat rest and clutch lever, mm	980	870
iii	Distance between seat rest and clutch lever, mm	1220	1100
iv	Distance between seat rest and main gear shift lever, mm	1200	1280
v	Distance between seat rest and rotary gear shift lever, mm	1300 to 953	1300
vi	Distance between seat rest and throttle lever, mm	805 to 546	630
vii	Distance of brake pedal form trailer seat	730	670

3.4 Vibration characteristics in stationary mode

Machine vibration at the root of handle bar and handle grip in stationary mode was measured for the walking tractor with and without improved work space layout using portable pulse multi-analyzer system (Brüel & Kjaer Type 3560 C). The machine vibration was measured using the ENDEVCO Istron model 751-10 accelerometer of the B & K instrument. Vibration signals in the vertical mode were recorded by employing Fast Fourier Transform (FFT) technique using the FFT analyzer built in the PULSE multi-analyzer system. FFT is a powerful analytical tool which transforms the random time domain data into highly descriptive frequency data. The trial was conducted at selected levels of engine rpm as (1500, 1750 and 2000 rpm). Each trial was repeated for three times with an acquisition period of 30 s, and the peak value arrived from the spectrum was averaged for each selected level of upper speed. The vibration from the handle of the walking tractor is transmitted to the hand and arm of the worker through the palm of his hand. The hand transmitted vibration was measured at handle-grip level as per the guide lines issued in ISO 5349 (1986). The transducer (B & K, Type 4392) mounted to be inserted between the fingers grip and the handles. The transducer is inserted between the middle and index fingers of left hand and between the middle and ring fingers for right hand. The orientation of the measurement axes of the accelerometer is as per the guide line stipulated in ISO 5349 (1986).

The hand transmitted vibration was measured for both modified and unmodified walking tractor-trailer in stationary and riding mode. Measurements were carried out at selected levels of engine speed of walking tractor. The pulse Programmer was activated after the walking tractor was started and the measurement was recorded with an acquisition period of 60 seconds. Each trial was repeated five times at selected levels of engine speed in stationary mode. The vibration characteristics of walking tractor handle is different while riding a walking tractor with an empty trailer. So vibration levels were measured on handle for walking tractor with and without improved system during transport on farm and bitumen road in same path but in virginal place. The measurement was taken at all selected levels of forward speed of operation in riding mode. Each trail was repeated for three times with an acquisition period of 30 s and the peak value arrived from the spectrum was averaged for each selected levels of forward speed. The exposure guideline was followed as per ISO 5349 (1986). The values of HTV of 5 runs were averaged at corresponding frequency for one subject in each rpm engine. The procedure was repeated for all the subjects and the mean value for each selected levels of engine was computed. The exposure time limit is then predicted by superimposing the mean measured values of 12 subjects at each frequency on the exposure guideline.

4 Results and discussion

4.1 Location of controls

In the existing design, the trailer is attached with the walking tractor through a single point hitch. The handle bar attached with the body of the walking tractor moves up and down while riding with the trailer. Accordingly, the height of the handle which varies from 610 to 950 mm of ground level (because of exchanging the position of handles during the riding mode) and this causes discomfort to the operator. In the walking tractor with improved work place layout, the handle bars are attached to the toe bar of the trailer and hence the height remains constant. In the existing design to negotiate turns, the operator has to lean side ways to hold the handle which swings to right or left as the turn may be.

The handle swings out of reach (the location of handle grip from the seat rest of trailer is 1,700 mm and the handle is inclined at 46° from the axis of trailer at extreme tuning condition). The operator jumps out of the seat and steers the walking tractor by holding the handle in standing posture from ground level improved the steering system. The lateral swing of the handle is arrested and the operator can steer the walking tractor with trailer from the seat of the trailer when negotiating turns. The specifications of the new steering system for walking tractor-trailer has been illustrated in Table 5.

Table 5 Specifications of with improved steering system for walking tracto –trailer

S. No.	Details	Value mm
i	Over all dimensions of the bracket fixed in toe bar of the trailer (L×B×H),	120×100×90
ii	Over all dimensions of the clamps fixed in bracket (L×B×H)	100×40×40
iii	Length of steering cable from steering clutch to the coupling	950
iv	Length of steering cable from the coupling to steering lever in the body of he walking tractor	1300
v	Over all dimensions of the frame connecting the lower end of the handle bar with trailer toe bar (L×B×H)	250×140×70
vi	Length of clutch rod	750

In the modified walking tractor location of controls *viz.*, steering clutch, main clutch lever, brake lever, main gear shift lever and rotary gear shift lever with reference to the seat of the operator is nearer when compared with the existing design. Hence the operator finds easy to reach the controls and operate the tractor trailer.

4.2 Machine vibrations of walking tractor with trailer in stationary and transporting mode

Machine vibration at the root of handle bar and handle grip in stationary mode was measured for the walking tractor with trailer and the peak value arrived from the spectrum was averaged for selected levels of engine speed and the values are furnished in Table 6.

It is observed that as the engine speed increased, the peak acceleration also increased at the root of handle bar and handle grip of walking tractor with trailer. The increase in engine rpm from 1,600 to 3,200 rpm resulted in three times increase in peak acceleration at root of the handlebar and more than two fold increases at handle grip

of walking tractor. The peak acceleration observed at the root of the handle bar and handle grip with walking tractor with improved steering system was lower than that of walking tractor-trailer without workplace layout. The magnitude of reduction varied from 5.2 to 19.7% and 13.9 to 30.7% at the root of the handle bar and handle grip respectively. The peak values of acceleration arrived from the vibration spectrum for walking tractor with and without improvement at selected forward speeds on farm road and bitumen road are shown in Table 7.

Table 6 Machine vibrations of walking tractor with trailer in stationary mode

Engine rpm	Peak acceleration, ms ⁻² modified&(unmodified)	
	Root of handle bar	Handle
	1600	4.24 (5.28)
1900	6.36 (7.40)	11.79 (15.49)
2200	7.55 (8.59)	13.24 (16.94)
2500	8.68 (9.72)	14.24 (17.94)
2700	10.03 (11.07)	17.39 (21.09)
3000	11.36 (12.40)	19.59 (23.29)
3200	12.35 (13.03)	21.37 (24.81)

Table 7 Machine vibration of walking tractor with trailer on transport mode

km/h	Peak acceleration, ms ⁻² modified&(unmodified)					
	Farm road			Bitumen road		
	Root of handle bar	Handle grip	Seat	Root of handle bar	Handle	Seat
3.5	3.96 (4.31)	4.41 (4.76)	1.38 (1.73)	3.77 (4.12)	3.41 (3.76)	1.01 (1.36)
4.0	4.61 (4.95)	5.15 (5.52)	1.39 (1.74)	4.38 (4.73)	4.93 (5.28)	1.07 (1.42)
4.5	4.98 (5.33)	6.51 (6.86)	1.47 (1.82)	4.72 (5.07)	5.37 (5.72)	1.33 (1.68)
5.0	5.12 (5.47)	6.72 (7.05)	2.56 (2.91)	4.77 (5.12)	5.39 (5.74)	1.45 (1.81)

The reduction of machine vibration at handle grip of the walking tractor with trailer having improved steering system was from 5.2% to 7.4% and from 6.1% to 9.3% on farm road and bitumen road respectively at selected levels of forward speed of operation.

The peak value of HTV in bitumen road was lower than that of farm road. This may probably due to the fact that unevenness and surface roughness of farm road induced more terrain vibrations compared to the relatively smooth level in bitumen road. The mean value of r.m.s weighted acceleration HTV of all subjects

at selected levels of forward speed for walking tractor with and without improved workplace layout during transport on farm road is presented in Table 8 as below:

Table 8 Mean value of root mean square acceleration (HTV) of all subjects

Speed (km/h)	Mean value of root mean square acceleration (HTV) (ms ⁻²)	Exposure time /h	Probability of white finger syndrome (years)
A Farm road			
3.5	2.31 (2.58)	2 - 4 (1-2)	9.45 (8.85)
4	2.67 (3.02)	1 - 2 (1-2)	8.19 (7.61)
4.5	3.09 (3.45)	1 - 2 (1/2 -1)	6.89 (6.17)
5	3.58 (3.98)	1/2 -1 (1/2-1)	5.88 (5.46)
B Bitumen road			
3.5	1.79 (2.02)	2 - 4 (2-4)	12.73 (10.50)
4	1.96 (2.35)	2 - 4 (2-4)	10.62 (9.27)
4.5	2.26 (2.64)	2 - 4 (1-2)	9.59 (8.48)
5	2.75 (3.12)	1 - 2 (1-2)	7.66 (6.85)

The value of hand transmitted vibration increased with the increase in forward speed on farm road and bitumen road respectively.

4.3 Turning radius

The measured values of turning radius for walking tractor-trailer with and without improved workplace layout are furnished in Table 9.

Table 9 Turning radius for walking tractor -trailer in different conditions

Serial No.	Forward speed /km · h ⁻¹	Turning radius, m	
		Walking tractor -trailer without improvement	Walking tractor -trailer with improvement
i	4	6.20	2.7
ii	5	6.74	2.8
iii	6	7.32	3.0

The turning radius for the modified walking tractor-trailer is smaller by 62.5 to 64.0%.

5 Conclusions

The core for omitting the vibrations is that it is better to slash the relation between the source of vibration and user part (handles). The ergonomic aspects of walking tractors are of great importance as working with walking tractor involves considerable physical strain to the operator. If ergonomic aspects are not given due consideration, the performance of the man-machine system will be poor and effective working time will be reduced. On the other hand, due to heavy demand on

the worker's biological systems, the walking tractor operation results in clinical and anatomical disorders and in the long run, will affect the workers' health. The man-machine environment system of walking tractor operation indicates that the operator of a walking tractor has to endure various environments and stresses. The environment includes all the factors in the surroundings which have an effect on man-machine system. Among these factors, environment is more important because it significantly accelerates fatigue and affects sensitivity and reaction rates of the operator. Physical efforts required for the operation of the machine combined with exposure to varying degrees of solar radiation, dusty environment, monotonous nature of the job and the severe hand vibrations cause a lot of stresses on the operator resulting in physiological and psychological fatigue after the daylong operation. The main clutch and brake lever form the handle bar of the walking tractor are connected to the clutch assembly through a rod and cable supported by clamps mounted on the left side handle bar. The two steering cables were extended in linear mode through a coupling mounted on the two sides of the bracket mounted on toe bar of the trailer. In the s with improvement the two handle bars are attached to the toe bar of the trailer. The vertical movement of the handle (from 610 to 950 mm) from ground level as observed in the existing design is arrested and this enables the operator to exercise firm grip of the handle. In the existing design to negotiate turns, the operator had to lean side ways to hold the handle which swings to right or left

as the turn may be. The handle swings out of reach (Distance of handle grip from the seat rest of trailer is 1,700 mm and the handle is inclined at 46° from the axis of trailer at extreme turning condition) and the operator jumps out of the seat and steers the walking tractor by holding the handle in standing posture from ground level. With improved steering system, the lateral swing of the handle is arrested and the operator can steer the walking tractor with trailer from the seat of the trailer when negotiating turns. The reduction of HTV at handle of the walking tractor with trailer having improved steering system was from 10.1 to 11.6% and from 11.9 to 17.3% on farm road and bitumen road respectively at selected levels of forward speed of operation. There was no variation in the safe exposure time of the operator with improved work space layout. However the probability of occurrence of finger blanching was increased from 6.4 to and 10.5 and 10.6 to 20.1% during transport on farm and bitumen road respectively with improved workplace layout. The turning radius for the walking tractor-trailer with improvement is smaller by 62.5 to 64.0% than that of walking tractor-trailer without improvement.

Acknowledgement

Appreciation is extended to ministry of science, research and technology, agricultural ministry (Iran), Director of ICCR, and Department of Farm Machinery, Agricultural Engineering Collage and Research Institute of TNAU (India), for providing necessary help in preparation of this manuscript.

References

- Borg, G. 1982. A category scale with ratio properties for intermodal and intraindividual comparisons in: Psychophysical Judgment and the Process of Perception (Petzold H G ed), pp. 25–34. Deutscher Verlag der Wissenschaften, Berlin.
- Broyde, et al. 2009. Characteristics of hand-transmitted vibration of a hand tractor used in three operational modes. *International Journal of Industrial Ergonomics*, 39(1): 239-245.
- Garg, A., K. Hegmann, and J. Kapellusch. 2006. Short-cycle overhead. Work and shoulder girdle muscle fatigue. *International Journal of Industrial Ergonomics*, 36, 581–597.
- Giacomina, et al. 2009. Effect of vibration isolators in reduction of work stress during field operation of hand tractor. *Biosystems Engineering*, 103(2): 146-158.
- Grandjean, E. 1982. Fitting the task to the man – an ergonomic approach. Taylor & Francis Ltd, London. pp. 77–81.
- Griffin, M. J. 1996. Hand book of human vibration. Academic Press, London
- ISO. 1986. Mechanical vibration-Guidelines for the measurement and the assessment of human exposure to hand transmitted vibration. ISO 5349-1986(E), International Organisation for

- Standardisation Geneva, Switzerland.
- ISO. 5349-a. 2001. Mechanical vibration measurement and evaluation of human exposure to hand-transmitted vibration, part I: General Requirements ISO 5349. International Standard Organization, Geneva
- ISO. 5349-b. 2001. Mechanical vibration-measurement and evaluation of human exposure to hand transmitted vibration, part 2: practical guidance for measurement at workplace, Geneva, Switzerland.
- Kuorinka, I. 1983. Subjective discomfort in a simulated repetitive task. *Ergonomics*, 26, 1089–1101.
- Mishoe and Suggs. 1977. Vibration effects on setting pregnant women—subjects of various masses. *Journal of Biomechanics*, 29(4): 493-501.
- Reynolds, D., R. H. Keith. 1977. Hand arm vibration, part I: analytical model of the vibration response characteristics of the hand. *Journal of Sound and Vibration*, 51(2): 237–252.
- Reynolds and Keith. 1977. A test rig for the measurement of vibration in hand-held power tools, *Biosystems Engineering*, 14(1): 11-18.
- Snook, S. H., V. M. Ciriello. 1991. The design of manual handling tasks: revised tables of maximum acceptable weights and forces. *Ergonomics*, 34(9): 1197–1213.
- Wasserman, and Taylor. 1991. Reducing vibration exposure from hand-held grinding, sanding and polishing powertools by improvement in equipment and industrial processes. *Biosystems Engineering*, Volume 25, 1-3, February-April 1997, Pages 143-152.
- Wos, H., T. Narek, C. Noworol, G. Borg 1988. The reliability of self ratings based on Borg's scale for hand–arm vibrations of short duration (part II). *International Journal of Industrial Ergonomics*, 2, 151–156.